

# Plastics America

## Safe-Tank Double-Wall Systems - HDXLPE

Plastics America Double-wall Polyethylene Tanks provide extra protection and a peace of mind in the event of a leak. These High Density Cross-linked Polyethylene Tanks eliminate the need to build large high maintenance concrete containment areas. The double-wall design features a containment area that will isolate reactive materials, protect employees and prevent environmental contamination in the event of a spill or leak.

Molded-in Lifting Lugs  
Standard on Tank Sizes > 500 Gallons



### Handy Conversions

- 1 IMP. = 1.2 US Gallons
- 1 US Gallon = 0.833 IMP Gallons
- 1 IMP Gallon = 4.546 Litres
- 1 US Gallon = 3.785 Litres
- 1 Litre = 0.22 IMP Gallons
- 1 Cu. FT = 6.23 IMP Gallons
- 1 Cu. FT = 7.48 US Gallons

[Click here for US to Imperial Gallon Conversions](#)

Stock Number	IMP GAL	Approx. O.D.	Approx. Overall Height	Lid Size
2000055				
2100085				
Assembly	46	3' - 0"	2' - 5"	5"
2000105				
2100150				
Assembly	88	3' - 0"	3' - 6"	5"
2000160				
2100220				
Assembly	133	3' - 0"	4' - 11"	5"
2000405				
2100445				
Assembly	338	4' - 0"	5' - 9"	5"
2000540				
2100665				
Assembly	450	6' - 5"	4' - 0"	19"
2001000				
2101200				
Assembly	833	6' - 5"	6' - 7"	19"
2001550				
2101950				
Assembly	1292	8' - 0"	6' - 11"	19"
2002500				
2103100				
Assembly	2083	8' - 0"	9' - 11"	19"
2003150				
2103550				
Assembly	2625	10' - 2"	7' - 7"	24"
2004400				
2104950				
Assembly	3667	10' - 3"	10' - 3"	24"
2005400				
2106300				
Assembly	4500	11' - 11"	9' - 9"	24"
2006650				
2107450				
Assembly	5542	10' - 2"	14' - 3"	24"
2008700				
2110150				
Assembly	7250	11' - 11"	14' - 6"	24"